

SPECIFICATION SHEET

Material – “Purbeck Cropped Walling Stone 100mm - 150mm Nom Bed”

Thickness on bed	-	100mm - 150mm nominal
Use	-	Retaining walls, facing to blockwork & cavity const.
Durability	-	Grade A (BRE269) complies with BS6349, BS812
Face Size	-	Heights - 65mm – 250mm Lengths - 100mm – 350mm
Weight	-	Aprox 4 M2 = 1 tonne
Bedding	-	1 ordinary Portland cement to 5 building sand. 1 of lime can also be added.
Pointing	-	1 ordinary Portland cement to 4 -5 building sand. 1 of lime can also be added.
Supplied	-	Loose or in 1 tonne bulk bags.
Price	-	Dependant on quantity & delivery destination.
Other	-	This material should be laid in its natural bed in random horizontal courses. Jumpers (larger stones) should be dotted around, aprox 2 – 3 per m2

Coshh

Care should be taken when handling this material. Edges can be sharp. Gloves & safety boots should be worn at all times. Good lifting practice should be observed. Larger slabs may be a two-man lift. If cutting this material, eye protection should be worn at all times.

	CALIFORNIA QUARRY, PANORAMA ROAD, SWANAGE, DORSET. BH19 2QS.	
	TEL: 01929 423576 FAX: 01929 427656	Visit our.. 