

SPECIFICATION SHEET

Material – “Imported Split Riven Handcut Flags”

Use	-	External paving, patios, terraces, and paths.
Thickness	-	25mm – 35mm aprox
Size	-	Supplied in a 3 size multicrate, 14no: of each size per crate. (280mm x 560mm, 560mm x 560mm & 560mm x 840mm) = 13.17m ² per crate.
Weight	-	1 x crate 13.17 m ² = 1 tonne (aprox)
Bedding	-	1 ordinary Portland cement to 6 - 8 sharp sand. 1 of lime can also be added. This paving should be laid on to a well-compacted base.
Pointing	-	1 ordinary Portland cement to 3 - 4 sharp Sand. 1 of lime can also be added. Solid flush pointing should be used so that no water can get into the joints.
Supplied	-	In Crates.
Other	-	There is a top face to these flags & they are intended to be laid the right way up. When you look at the slabs from the edge. They are slightly wedge shaped. The widest side is the top face. When laying remove any dust from the underside of the slab & ensure that the bedding medium is wet enough to dampen the underside of the slab. This will help the bedding adhere to the flag. Never use acid cleaners on this material

Coshh

Care should be taken when handling this material. Edges can be sharp. Gloves & safety boots should be worn at all times. Good lifting practice should be observed. Larger slabs may be a two-man lift. If cutting this material, eye protection should be worn at all times.

	CALIFORNIA QUARRY, PANORAMA ROAD, SWANAGE, DORSET. BH19 2QS.	
	TEL: 01929 423576 FAX: 01929 427656	Visit our.. 