

SPECIFICATION SHEET

Material – “Riven New Vein Purbeck Paving Flags”

Use	-	Patios, terraces, paths and driveways
Thickness	-	40mm – 85mm
Size	-	300mm – 400mm – 500mm widths x Random lengths (300mm – 750mm)
Weight	-	Aprox 6 M2 = 1 tonne (aprox)
Bedding	-	1 ordinary Portland cement to 6 - 8 sharp Sand. 1 of lime can also be added. This paving should be laid on to a well-compacted base.
Pointing	-	1 ordinary Portland cement to 3 - 4 sharp Sand. 1 of lime can also be added.
Supplied	-	Shrink wrapped on pallets.
Price	-	£65 per m2 + vat & delivery
Other	-	There is a top face to these slabs. This is the tidier & more even side. When laying remove any dust or clay from the underside of the slab & ensure that the bedding medium is wet enough to dampen the underside of the slab. This will help adhesion.

Coshh

Care should be taken when handling this material. Edges can be sharp. Gloves & safety boots should be worn at all times. Good lifting practice should be observed. Larger slabs may be a two-man lift. If cutting this material, eye protection should be worn at all times.

	CALIFORNIA QUARRY, PANORAMA ROAD, SWANAGE, DORSET. BH19 2QS.	
	TEL: 01929 423576 FAX: 01929 427656	Visit our.. 